IN THE CLAIMS:

1.    (currently amended)      In a network of Bluetooth protocol devices, a method for establishing communications comprising:

prior to broadcasting a piconet beacon frequency, establishing a piconet with a master device;

the master device broadcasting a piconet beacon frequency at a first predetermined frequency f(k$_B$) from a plurality of spread spectrum transmission frequencies, wherein the piconet beacon frequency includes the master device's Bluetooth address (BD_addr) and clock (CLK) information;

monitoring to receive the piconet beacon frequency; and

in response to receiving the piconet beacon frequency, establishing communications with the piconet.


2-3.    canceled


4.    (currently amended)      The method of claim [[3]] 1 wherein receiving the piconet beacon frequency includes an inquiring device receiving the BD_addr and CLK information of the master device.


5.    (original)     The method of claim 4 wherein receiving the piconet beacon frequency includes the inquiring device receiving the BD_addr and CLK information of the master device in a first downlink frequency hop synchronization (FHS) packet.


sla1003_response_1.doc                2

6.    (currently amended)      The method of claim 5 wherein establishing communications with the piconet includes the inquiring device deriving [[the]] a master device frequency hopping sequence from the master device BD_addr and master device CLK information.

7.    (original)    The method of claim 6 wherein establishing communications includes, following the receiving of the first downlink FHS packet by the inquiring device, transmitting a first uplink FHS packet from the inquiring device to the master device.

8.    (currently amended)      The method of claim 7 wherein transmitting a first uplink FHS packet from the inquiring device to the master device includes transmitting [[the]] an inquiring device BD_addr in the FHS packet payload.

9.    (original)    The method of claim 8 wherein transmitting a first uplink FHS packet from the inquiring device to the master device includes transmitting a FHS packet access code (AC) derived from the master device BD_addr.

10.    (original)    The method of claim 9 wherein establishing communications includes, following the receiving of the first uplink FHS packet by the master device, transmitting a second downlink FHS packet from the master device to the inquiring device.

sla1003_response_1.doc                3

11.    (original)    The method of claim 10 wherein transmitting a second downlink FHS packet from the master device to the inquiring device includes transmitting an active member address (AM_addr) in the FHS packet payload.

12.    (original)    The method of claim 11 wherein transmitting a second downlink FHS packet from the master device to the inquiring device includes transmitting a FHS packet access code derived from the inquiring device BD_addr.

13.    (currently amended)    The method of claim 12 wherein establishing communications includes, following [[the]] a receiving of the second downlink FHS packet by the inquiring device, transmitting an ID packet from the inquiring device to the master device, acknowledging [[the]] a receipt of the AM_addr.

14.    (currently amended)    The method of claim 13 wherein establishing communications includes:

following [[the]] a receiving of the ID packet by the master device, transmitting a POLL packet from the master device to the inquiring device;

in response to receiving the POLL packet, transmitting a NULL packet from the inquiring device to the master device; and

establishing higher level protocols between the master device and the inquiring device.

sla1003_response_1.doc                    4

15.    (original)    The method of claim 14 wherein establishing higher level protocols between the master device and the inquiring device includes the inquiring device becoming a piconet slave device.

16.    (currently amended)    The method of claim 15 wherein broadcasting a piconet beacon frequency includes the master device broadcasting the first downlink FHS packet in [[the]] a slot at frequency $f(k_B)$;

wherein transmitting the first uplink FHS packet includes:

the inquiring device randomly selecting a number m, where m is a number between 1 to 8 for [[the]] a contention period of 15 slots;

the inquiring device transmitting the first uplink FHS packet in the slot at frequency $f(k_B + (2m-1))$;

wherein the master device transmits the second downlink FHS packet in the slot at frequency $f(k_B + 2m)$; and,

wherein the inquiring device transmits the ID packet in the slot at frequency $f(k_B + (2m+1))$.

17.    (original)    The method of claim 16 wherein the inquiring device randomly selecting a number m includes randomly selecting a number m between 1 to 8; and,

the method further comprising:

establishing a contention period equal to fifteen slots; and

the master device waiting (2m-1) slots from the broadcast of the piconet beacon frequency at frequency $f(k_B)$ to receive a first uplink FHS packet from an inquiring device.

sla1003_response_1.doc                    5

18.    (original)    The method of claim 16 further comprising:

establishing a contention period equal to fifteen slots; and

the master device waiting a maximum of fifteen slots from the broadcast of the piconet beacon frequency at frequency $f(k_B)$ to receive a first uplink FHS packet from an inquiring device.

19.    (original)    The method of claim 1 further comprising:

establishing a piconet with a master device; and

wherein broadcasting a piconet beacon frequency includes the master device broadcasting at a first plurality of predetermined beacon frequencies from the plurality of spread spectrum transmission frequencies;

wherein monitoring for the piconet beacon frequency includes monitoring the first plurality of beacon frequencies; and

wherein establishing communications with the piconet includes establishing communications in response to receiving one of the plurality of piconet beacon frequencies.

20.    (currently amended)    In a network of Bluetooth protocol devices, a method for a master device to permit the establishment of piconet communications comprising:

a master device broadcasting a piconet beacon frequency in a first downlink FHS packet including the master device's BD addr and

CLK information, at a first predetermined frequency f(k_B) from [[the]] a

plurality of spread spectrum transmission frequencies; [[and,]]

      receiving a first uplink FHS packet from an inquiring device,

in response to broadcasting the piconet beacon frequency, wherein the

first uplink FHS packet includes the inquiring device BD_addr in the FHS

packet payload and a FHS packet access code (AC) derived from the

master device BD_addr; and

      following the receiving of the first uplink FHS packet by the

master device, transmitting a second downlink FHS packet from the

master device to the inquiring device.


      21-23. canceled


      24.   (currently amended)     The method of claim [[23]]

20 wherein transmitting a second downlink FHS packet from the master

device to the inquiring device includes transmitting an AM_addr in the

FHS packet payload.


      25.   (original)     The method of claim 24 wherein

transmitting a second downlink FHS packet from the master device to the

inquiring device includes transmitting a FHS packet access code derived

from the inquiring device BD_addr.


      26.   (original)     The method of claim 25 further

comprising:

following the transmission of the second downlink FHS

packet by the master device, receiving an ID packet from the inquiring

device acknowledging the receipt of the AM_addr.


27.    (currently amended)      In a network of Bluetooth

protocol devices, a method for an inquiring device to establish

communications with a piconet, the method comprising:

monitoring to receive the piconet beacon frequency at a first

predetermined frequency f(k$_B$) from [[the]] a plurality of spread spectrum

transmission frequencies, wherein the piconet beacon frequency includes a

master device Bluetooth address (BD_addr) and clock (CLK) information

in a first downlink FHS packet; [[and]]

in response to receiving the piconet beacon frequency,

transmitting a first uplink frequency hop synchronization (FHS) packet to

establish communications with the piconet, wherein FHS packet includes

the inquiring device BD_addr in the FHS packet payload and a FHS

packet access code (AC) derived from the master device BD_addr;

following the transmission of the first uplink FHS packet,

receiving a second downlink FHS packet from the master device including

an active member address (AM_addr) in the FHS packet payload and a

FHS packet access code derived from the inquiring device BD_addr; and

deriving the master device frequency hopping sequence from

the master device BD_addr and master device CLK information.


28-31. canceled


sla1003_response_1.doc                    8

32.    (currently amended)       The method of claim [[31]] 27 further comprising:

following the receiving of the second downlink FHS packet by the inquiring device, transmitting an ID packet to the master device, acknowledging the receipt of the AM_addr.

33.    (currently amended)       A system for establishing communications in a network of Bluetooth protocol devices, the system comprising:

a master device broadcasting a piconet beacon frequency, the piconet beacon frequency including the master device's Bluetooth address (BD_addr) and clock (CLK) information;

at least one inquiring device monitoring the piconet beacon frequency, and in response to receiving the piconet beacon frequency, establishing communications with the master device.

34.    (currently amended)       The system of claim 33 wherein the master device broadcasts the piconet beacon frequency at a first predetermined frequency $f(k_B)$ from among [[the]] a plurality of spread spectrum broadcast frequencies.

35.    (original)       The system of claim 33 wherein the master device broadcasts the piconet beacon frequency at a first plurality of predetermined frequencies from among the plurality of spread spectrum broadcast frequencies; and,

sla1003_response_1.doc                9

wherein the inquiring device monitors the first plurality of piconet beacon frequencies and, in response to receiving one of the piconet beacon frequencies, establishes communications with the master device.

36.    canceled

37.    (currently amended)    The system of claim [[36]] 34 wherein the inquiring device receives the BD_addr and CLK information of the master device in a first downlink frequency hop synchronization (FHS) packet broadcast on the piconet beacon frequency.

38.    (currently amended)    The system of claim 37 wherein the inquiring device derives [[the]] a master device frequency hopping sequence from the master device BD_addr and CLK information received on the piconet beacon frequency.

39.    (original)    The system of claim 38 wherein the inquiring device transmits a first uplink FHS packet to the master device following the reception of the first downlink FHS packet.

40.    (currently amended)    The system of claim 39 wherein the inquiring device transmits a first uplink FHS packet to the master device including [[the]] an inquiring device BD_addr in the FHS packet payload.

41.    (original)    The system of claim 40 wherein the inquiring device transmits a first uplink FHS packet to the master device

slal003_response_1.doc                    10

including a FHS packet access code (AC) derived from the master device BD_addr.

42.    (original)    The system of claim 41 wherein the master device transmits a second downlink FHS packet to the inquiring device following the reception of the first uplink FHS packet.

43.    (original)    The system of claim 42 wherein the master device transmits a second downlink FHS packet to the inquiring device including an active member address (AM_addr) in the FHS payload.

44.    (original)    The system of claim 43 wherein the master device transmits a second downlink FHS packet to the inquiring device including a FHS packet access code derived from the inquiring device BD_addr.

45.    (currently amended)    The system of claim 44 wherein the inquiring device transmits an ID packet to the master device following [[the]] a reception of the second downlink FHS packet, acknowledging [[the]] a receipt of the AM_addr.

46.    (currently amended)    The system of claim 45 wherein the master device transmits a POLL packet to the inquiring device following [[the]] a receipt of the ID packet by the master device;
        wherein the inquiring device transmits a NULL packet to the master device in response to receiving the POLL packet; and,

sla1003_response_1.doc                    11

wherein the master device establishes higher level protocols with the inquiring device following the receipt of the NULL packet.


47.    (original)    The system of claim 46 wherein the inquiring device becomes a piconet slave device following the establishment of higher level protocols with the master device.


48.    (currently amended)    The system of claim 47 wherein the master device broadcasts the first downlink FHS packet in [[the]] a slot at frequency $f(k_B)$;

wherein the inquiring device randomly selects a number m, and transmits the first uplink FHS packet in the slot at frequency $f(k_B +(2m-1))$;

wherein the master device transmits the second downlink FHS packet in the slot at frequency $f(k_B +2m)$; and,

wherein the inquiring device transmits the ID packet in the slot at frequency $f(k_B +(2m+1))$.


49.    (original)    The system of claim 48 in which a contention period equal to fifteen slots is established;

wherein the inquiring device randomly selecting a number m includes randomly selecting a number m between 1 to 8; and,

wherein the master device waits $(2m-1)$ slots from the broadcast of the piconet beacon frequency at frequency $f(k_B)$ to receive a first uplink FHS packet from an inquiring device.


sla1003_response_1.doc                    12

50.    (original)    The system of claim 49 in which a contention period equal to fifteen slots is established;

.wherein the master device waits a maximum of fifteen slots from the broadcast of the piconet beacon frequency at frequency f(k_B) to receive a first uplink FHS packet from an inquiring device.

51.    (currently amended)    A Bluetooth protocol piconet master device comprising:

a transmitter broadcasting a piconet beacon frequency <u>at a first predetermined frequency f(k_B) from among a plurality of spread spectrum broadcast frequencies, wherein the piconet beacon frequency includes a first downlink frequency hop synchronization (FHS) packet with the master device Bluetooth address (BD_addr) and clock (CLK) information</u>; and,

a receiver to receive communications from an inquiring device monitoring the piconet beacon frequency to establish communications with the master device.

52-53. canceled

54.    (currently amended)    The master device of claim [[53]] <u>51</u> wherein the receiver receives a first uplink FHS packet, including the BD_addr of the inquiring device following the transmission of the first downlink FHS packet.

sla1003_response_1.doc          13

55.    (currently amended)        A Bluetooth protocol device inquiring to establish communications with a piconet, the inquiring device comprising:

a receiver having an input to monitor and receive a piconet beacon frequency at a first predetermined frequency f(kB) from among a plurality of spread spectrum broadcast frequencies, wherein the piconet beacon frequency includes a first downlink frequency hop synchronization (FHS) packet with the master device Bluetooth address (BD_addr) and clock (CLK) information; and

a transmitter having an output to establish communications with a piconet master device in response to receiving the piconet beacon frequency.

56-57. canceled

58.    (currently amended)        The inquiring device of claim [[57]] 55 wherein the inquiring device derives the master device frequency hopping sequence from the master device BD_addr and CLK information received on the piconet beacon frequency.

59.    (original)    The inquiring device of claim 58 wherein the transmitter transmits a first uplink FHS packet, including its BD_addr, to the master device following the reception of the first downlink FHS packet.

sla1003_response_1.doc                    14